S9033RT/S9043RT/S9053RT

LARGE DECK, ROUGH TERRAIN SCISSOR LIFTS



- Large deck rough terrain scissor lifts
- Excellent rough terrain performance
- Easy to operate
- Heavy duty design
- Ideal for construction applications




LARGE DECK, ROUGH TERRAIN SCISSOR LIFTS

DIMENSIONS	S9033RT*	S9043RT*	S9053RT*
Max. working height	11.8m	15.1m	17.9m
Max. platform height (A)	9.8m	13.1m	15.9m
Platform size (stowed)		3.58m x 2.28m	
Platform size (single deck extended)		4.95m x 2.28m	
Platform size (dual deck extended)		6.7m x 2.28m	
Extension deck length	1.37m	1.37m	1.37m
Overall width (B)	2.28m	2.28m	2.28m
Overall length (D)	3.68m	3.68m	3.68m
Stowed height (C)	2.97m	2.99m	3.2m
Min. height (guardrails folded)	1.98m	2.18m	2.33m
Ground clearance	381mm	381mm	381mm


PERFORMANCE				
Platform capacity (SWL)	1,134kg	680kg	680kg	
Max. drive height	9.8m	13.1m	9.1m	
Max. wind speed	12.5m/s	12.5m/s	12.5m/s	
Max. drive speed (stowed)	6.7km/h	6.7km/h	6.7km/h	
Max. drive speed (elevated)	0.9km/h	0.9km/h	0.9km/h	
Raise/lower time	45/30 sec	50/35 sec	55/40 sec	
Gradeability	50%	50%	50%	
Max. stabilizer levelling, front to rear	7°	7°	7°	
Max. stabilizer levelling, side to side	14°	14°	14°	
Inside turning radius	2.03m	2.03m	2.03m	
Outside turning radius	5.28m	5.28m	5.28m	
Tires	12 x 33 foam filled			
Controls	proportional joystick			
Drive system	4 wheel drive			

POWER				
Power source		Kubota diesel		
WEIGHT				
Weight	5,443kg	6,350kg	7,484kg	

TURNING RADIUS



\$9033RT/ \$9043RT/\$9053RT



STANDARD FEATURES

- 4 wheel drive
- 4 hydraulic outriggers with automatic levelling (S9053RT only)
- Single manual roll-out deck extension
- Proportional controls
- Foam filled tires
- Power line to platform
- Drive motion alarm
- Descent alarm
- Locking articulating axle
- Manual lowering valve
- Flashing amber light
- Dual lanyard attachment points
- Hour meter & on-board diagnostics display
- 2 year parts & labor, 5 year structural warranty
- ANSI compliant

OPTIONS

- Special paint colors
- Nylon spreader pads (set of 4)
- Environmental hydraulic oil
- Dual fuel
- LPG power
- Cold weather package (block heater + battery warm up)
- Single powered extension deck
- Dual powered extension decks
- Hydraulic 2kW generator
- Hydraulic 12kW generator
- 4 hydraulic outriggers with automatic levelling (S9033RT + S9043RT only)



P.O. Box 1160 St.Joseph, MO 64502-1160, USA Tel: 1 (785) 989-3000 Toll-free: 1 (800) 255-0317 Fax: 1 (785) 989-3070

Email: sales.usa@snorkellifts.com